



G-1183-18E2-C, Contactor SPDT Center Off NSN: 5945-00-226-6182



Actual product may differ from image shown.

Product Overview:

- Mains SPDT Center off
- Rated for 50amps AC
- 50,000 cycles at rated load / 300,000 cycles at half rated load
- Hermetically sealed
- Contact NPAS for specific needs and customizable options.



Performance Specifications

Coil Data		Contact Data	
Nominal Voltage	28VDC	Main	
Pickup	18VDC max	SPDT CO	
Dropout	10 - 3 VDC	Auxiliary	
Coil Resistance	160Ω ±20%	N/A	
Coil Current	-	Life (cycles)	28VDC (amps)
Suppression	-	50,000	-
Duty	Continuous	50,000	-
Electrical Data		50,000	-
Insulation Resistance	≥100MΩ @ 500VDC min	-	-
Dielectric Strength (sea level)	-	-	-
Contacts to Ground	1500Vrms	-	-
Between contacts	1500Vrms	-	-
Coil to Ground	1050Vrms	-	-
Environmental		-	-
Temperature range	-65°F to +160°F	-	-
Altitude	50,000 ft. max	-	-
Shock	-	-	-
Vibration, sinusoidal	-	-	-
Arrangement		Mechanical Data	
Rating		125mV max	
Resistive		Contact Resistance	
Inductive		Timing	
Motor		Release	
Lamp		Transfer	
Rupture		Bounce	
Mechanical		Mechanical Data	
Voltage Drop		Weight	
Contact Resistance		12.8 oz.	
Timing		Specifications IAW	
Release		Meets materials and workmanship requirements of MIL-PRF-6106	
Transfer			
Bounce			