




GDB-1830, Contactor, 3PDT, 60 Amp 115/208VAC, 400Hz NSN: 5945-00-868-4413



Product Overview:

- 3PDT Side Stable
- Rated for 60 Amps, AC
- Meets many requirements of MIL-PRF-6106
- Contact NPAS for specific needs and customizable options.



Performance Specifications

Coil Data			Contact Data					
Nominal Voltage	28VDC	Arrangement	Main			Auxiliary		
Pickup	18VDC @ 71°C		3PDT, Side Stable			SPST NC		
Dropout	7 - 1.5 VDC		Life (cycles)	28VDC (amps)	208VAC (amps)	Life (cycles)	28VDC (amps)	115VAC (amps)
Coil Resistance	-		50,000	-	60	50,000	5	5
Coil Current	-		-	-	-	-	-	-
Suppression	-	Motor	-	-	-	-	-	-
Duty	Continuous	Lamp	-	-	-	-	-	-
Electrical Data		Rupture	-	-	450	-	-	-
Insulation Resistance	≥100MΩ @ 500VDC min	Mechanical	100,000	-	-	-	-	-
Dielectric Strength (sea level)		Voltage Drop	200mV					
Contacts to Ground	1500Vrms	Contact Resistance	-					
Between contacts	1500Vrms	Timing	-					
Coil to Ground	1050Vrms	Release	-					
Environmental		Transfer	-					
Temperature range	-55°C to +71°C	Bounce	-					
Altitude		Mechanical Data						
Shock		Weight	14 oz.					
Vibration, sinusoidal	Proc I, MIL-E-5272	Specifications IAW	Meets materials and workmanship requirements of MIL-PRF-6106					