



517353,Relay, NSN: 5945-00-583-5193



Product Overview:

- Low amperage activation
- 2 amps resistive load at 30VDC
- Contact NPAS for specific needs and customizable options.



Performance Specifications

Coil Data		Contact Data						
Nominal Voltage	-	Arrangement Rating Resistive Inductive Motor Lamp Rupture Mechanical Voltage Drop Contact Resistance Timing Release Transfer Bounce Mechanical Data Weight Specifications IAW	Main			Auxiliary		
Pickup	7.5 mA max		DPDT			N/A		
Dropout	3.1 mA min		Life (cycles)	30VDC (amps)	200VAC (amps)	Life (cycles)	28VDC (amps)	115VAC (amps)
Coil Resistance	700Ω ± 10%		50,000	2	-	-	-	-
Coil Current	-		-	-	-	-	-	-
Suppression	-		-	-	-	-	-	-
Duty	-		-	-	-	-	-	-
Electrical Data			-	-	-	-	-	-
Insulation Resistance	≥10,000MΩ @ 500VDC min	100,000	-	-	-	-	-	
Dielectric Strength (sea level)	-							
Contacts to Ground	1050Vrms							
Between contacts	1050Vrms							
Coil to Ground	1050Vrms							
Environmental								
Temperature range	-							
Altitude	-							
Shock	-							
Vibration, sinusoidal	-							