




GDB-1872, Relay SPDT, 25 amp NSN: 5945-01-034-9909



Actual product may differ from image shown.

Product Overview:

- AC rated coil up to 125VAC
- Continuous duty, 25 amps AC
- Contact NPAS for specific needs and customizable options.



Performance Specifications

Coil Data		Contact Data						
Nominal Voltage	115VAC, 400Hz.	Arrangement Rating	Main			Auxiliary		
Pickup	90VAC max		SPDT			N/A		
Dropout	60 - 40 VAC		Life (cycles) min	28VDC (amps)	115VAC (amps)	Life (cycles)	28VDC (amps)	115VAC (amps)
Coil Resistance	-		10,000	-	25	-	-	-
Coil Current	.1amps @ 115VAC		10,000	-	15	-	-	-
Suppression	-		10,000	-	20	-	-	-
Duty	Continuous		-	-	-	-	-	-
Electrical Data			Rupture	-	-	-	-	-
Insulation Resistance	≥100MΩ @ 500VDC min		Mechanical	-	-	-	-	-
Dielectric Strength (sea level)			Voltage Drop	125mV				
Contacts to Ground	1250Vrms	Contact Resistance	-					
Between contacts	1250Vrms	Timing	-					
Coil to Ground	1250Vrms	Release	-					
Environmental		Transfer	-					
Temperature range	-	Bounce	-					
Altitude	-	Mechanical Data						
Shock	-	Weight	.7 lbs.					
Vibration, sinusoidal	-	Specifications IAW	Meets materials and workmanship requirements of MIL-R-6106					