

Coil Data		Arrangement	Contact Data					
Nominal Voltage	115VAC		Main			Auxiliary		
Pickup	.45a max with 50 Watt Lamp		DPST, N.C.			N/A		
Dropout	-		Life (cycles)	28VDC (amps)	115VAC (amps)	Life (cycles)	28VDC (amps)	115VAC (amps)
Coil Resistance	-		Resistive	-	-	-	-	-
Coil Current	.45a max with 50 Watt Lamp		Inductive	-	-	-	-	-
Suppression	-		Motor	-	-	-	-	-
Duty	-	Lamp	50,000	-	.84	-	-	-
Electrical Data		Rupture	-	-	-	-	-	-
Insulation Resistance	≥100MΩ @ 1000VDC min	Mechanical	100,000	-	-	-	-	-
Dielectric Strength (sea level)		Voltage Drop	-					
Contacts to Ground	1250Vrms	Contact Resistance	-					
Between contacts	1250Vrms	Timing	-					
Coil to Ground	1250Vrms	Release	-					
Environmental		Transfer	-					
Temperature range	-	Bounce	-					
Altitude	-	Mechanical Data	-					
Shock	-	Weight	-					
Vibration, sinusoidal	-	Specifications IAW	Meets materials and workmanship requirements of MIL-PRF-5757					